



Product Service

CERTIFICATE

No. Z2 074342 0048 Rev. 00

Holder of Certificate: **GSWeb Co., Ltd**

65, Saengnim-daero, 259 beon-gil, Saengnim-myeon
Gimhae-si, Gyeongsangnam-do 50802
REPUBLIC OF KOREA

Certification Mark:



Product: **Playground equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 028-713300072-0042

Valid until: 2030-01-23

Date, 2025-01-24

Zwickl R

(Roland Zwickl)

CERTIFICATE

No. Z2 074342 0048 Rev. 00

Model(s):

**GS-N101, GS-N101-1, GS-N110, GS-N201, GS-N201-1,
 GS-N301, GS-N301-1, GS-N310, GS-RH15X08, GS-
 RH19X13, GS-RH19X19, GS-RH23X19, GS-RH101, GS-
 RH103, GS-RH104, GS-RH105, GS-RH106, GS-RH107,
 GS-RH112, GS-RH115, GS-RH115-M, GS-RH201, GS-
 RH202, GS-RH301, GS-RH302, GS-RH401, GS-RH402**

Parameters:

Base: curved Pipe system with nets; hammock elements;
 double Slide and vertical climbing ropes
 Ropes consist of steel-loaded polyamide
 cables with UV guard.

Dimension:

Rope: 18 and 20 mm. Ropes consist of steel-loaded

Polyamide cables with UV guard.

Pipe: Hot Zinc galvanized and powder painted.

Ø 267 mm, 4 x 6 mm baseframe; Ø 165 mm, 2 x 4 mm
 netring center;

Ø 114 mm, 3 x 4 mm netrings small

Slide made of stainless steel.

GS-RH105 additional:

Woodenpost made of robinia Ø 150-200 mm length 5 — 6 meters.

GS-RH402 additional:

Nets are spanned between the poles and anchors at the ground. The space nets are designed like pyramids.

Model	Length (mm)	Width (mm)	Height (mm)	Max. falling Height (mm)
GS-N101	13750	8810	6020	2090
GS-N101-1	7800	2550	4410	1550
GS-N110	11000	6900	2800	2700
GS-N201	11720	6400	4700	2960
GS-N201-1	4260	3050	1540	1540
GS-N301	15830	8670	4940	2850
GS-N301-1	8880	6720	4940	2850
GS-N310	10000	5100	5000	1000
GS-RH15X08	11000	3700	2800	2800
GS-RH19X13	15000	10000	2900	2900
GS-RH19X19	14000	14000	2900	2900



CERTIFICATE

No. Z2 074342 0048 Rev. 00

GS-RH23X19	18000	16000	2900	2900
GS-RH101	34460	31390	2470	2470
GS-RH103	23190	14960	2900	2900
GS-RH104	19840	6390	2870	2870
GS-RH105	19280	16640	5010	2600
GS-RH106	18150	16920	5620	2380
GS-RH107	10400	7820	5900	2070
GS-RH112	10040	7130	2280	1970
GS-RH115	4140	2600	2000	2000
GS-RH115-M	4200	2600	2000	2000
GS-RH201	5680	4830	2070	1300
GS-RH202	4340	1630	2100	1360
GS-RH301	6220	3120	2450	2450
GS-RH302	9220	3120	2450	2450
GS-RH401	6000	4200	2500	2300
GS-RH402	18000	10200	5100	1800

**Tested
according to:**

EN 1176-1:2017/A1:2023
EN 1176-3:2017
EN 1176-11:2014